

UniStrong

P9

High Performance Handheld Terminal System



* NOTES: P9 includes P9 and P9 Pro. Just P9 Pro support camera, internal GPS and WCDMA network.
P9 doesn't support.

Parameter details

Model	P 9
Physical parameter	
Operation system	Windows Mobile 6.5
Processor	TI Sitara™ AM335x 1GHz
RAM	512Mb
ROM	8GB board flash memory (32GB as option)
Screen	3.7inch Blanview TFT transfective screen, 640x480 VGA resolution ratio
Battery	7.2V/3400mAh removable,single battery endurance>10hours
Bluetooth	Bluetooth,version 2.1+EDR, USB OTG (directly conenct Uflash disk), serial port, DC jack
Camera (optional)	5megapixels automatic focusing VGA resolution ratio video
Communica- -tion (optional)	3.5G WCDMA 900/2100MHz
GNSS (optional)	GPS + GLONASS/ 72 channels
WI-FI	WLAN 802.11b/g
Press button	All digital alphabet multi-function keyboard, F1-F4 definable shortcuts, lateral definable collect keys
Size	Length 192.0mm Width 93.5mm thickness 43.0mm
Weight	600g (without battery)
Environment	
Protection level	IP 67
Temperature	Operation temperature -30°C-+60°C, Storage temperature -30°C-+70°C
Humidity	5%-95%Rh non-condensing
Drop	2meters fell on the cement plywood ground without damage